

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 1/8

**1 - IDENTIFICATION**

Product identifier:	SL300 Vulk Cement Multipurpose
Other means of identification:	475006
Recommended use of the chemical and restrictions on use:	In the process of retreading tires using the autoclave and hot methods, in repairing pits, in applying hot patches and in repairing inner tubes using the hot method. <b>Restrictions on use:</b> This product should not be used for applications other than those recommended in this section. For more information, consult the product's technical data sheet.
Manufacturer's name:	Vipal Rubber Corporation
Address:	2601 NW 89, FL 33172 - Miami - FL - United States.
Telephone number:	+1 305 640 0330
Emergency phone number:	+1 305 640 0330

**2 - HAZARD IDENTIFICATION**

Classification of the chemical:	Flammable Liquids - Category 2; Skin Corrosion/Irritation - Category 2; Specific Target Organ Toxicity – Single Exposure - Category 3 - Narcotic.
Classification system adopted:	OSHA HCS 29 CFR 1910.1200 Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.
Pictograms:	



Signal word:	DANGER
Hazard statement(s):	Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness.
Precautionary statement(s):	<b>PREVENTION:</b> Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  <b>RESPONSE TO EMERGENCY:</b> If on skin: Wash with plenty of water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor, if you feel unwell. Get medical advice/attention. Specific treatment. If skin irritation occurs: If skin irritation occurs: Get medical advice/attention.

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 2/8

Wash with plenty of water.  
Take off contaminated clothing.  
Take off contaminated clothing and wash it before reuse.  
And wash it before reuse.

**STORAGE:**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**DISPOSITION:**

Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: The product has no other hazards.

Any hazards not otherwise classified that have been identified during the classification process: Hazardous to the Aquatic Environment - Acute Hazard - Category 2.  
Hazardous to the Aquatic Environment - Chronic Hazard - Category 2.

**3 - COMPOSITION/INFORMATION ON INGREDIENTS****MIXTURE**

Components contributing to the hazard:

Product identifier	CAS/EC	Concentration range (%)
Naphtha (petroleum), full-range straight-run	64741-42-0 265-042-6	48.80 - 73.20
Sulfur	7704-34-9 231-722-6	0.15 - 0.23

**4 - FIRST-AID MEASURES****Description of necessary measures**

**Inhalation:** Remove victim to fresh air and keep in a position that does not obstruct breathing. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.

**Skin contact:** Wash exposed skin with sufficient amount of water to remove the product. Remove and isolate contaminated clothing and shoes. In case of skin irritation: Consult a doctor. Bring this document.

**Eye contact:** Rinse carefully with water for several minutes. If wearing contact lenses, remove them if it is easy and keep rinsing. If eye irritation persists: consult a doctor. Bring this document.

**Ingestion:** Wash the victim's mouth with plenty of water. Never give anything by mouth to an unconscious person. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.

**Most important symptoms/effects, acute and delayed:** Causes skin irritation with redness, pain and dryness. May cause drowsiness or dizziness, may cause dizziness and nausea.

**Indication of immediate medical attention and special treatment needed, if necessary:** Avoid contact with the product when helping the victim. If necessary, symptomatic treatment should include, above all, supportive measures such as correction of hydro electrolytic and metabolic disorders and respiratory assistance. In case of skin contact, do not rub the affected area.

**5 - FIRE-FIGHTING MEASURES**

**Extinguishing media:** Appropriate: Compatible with all means of extinguishing.

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00	Date: 03/03/2025	Pages: 3/8
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as: sparks, open flames or flames from matches and cigarettes, welding operations, pilot lights and electric motors. May build up static charge by flow or agitation. Vapors from heated product can ignite by static discharge. Vapors are denser than air and tend to accumulate in low-lying or confined areas such as storm drains and basements. It can travel great distances causing the flame to retreat or new fires in both open and confined environments. Containers may explode if heated.	
Special protective actions for fire-fighters:	If the load is involved in fire, isolate and evacuate the area to a minimum radius of 800 meters. Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing. Containers and tanks involved in the fire must be cooled with water mist.	

**6 - ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment, and emergency procedures:	<b>For non-emergency personnel:</b> Isolate the leakage from sources of ignition. Keep unauthorized persons out of the area and away from windows. Stop the leakage if it can be done without risk. Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled product without proper clothing. Avoid exposure to the product. Stay in a safe place, with the wind at your back. Use personal protective equipment as described in section 8. <b>For emergency responders:</b> Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask. <b>Emergency procedures:</b> Avoid that the spilled product reaches waterways or sewage system.
Methods and materials for containment and cleaning up:	Use water mist to reduce the dispersion of vapors. Use natural or spill containment barriers. Collect spilled products and place them in appropriate containers. Adsorb the remaining product with dry sand, earth, vermiculite, or any inert product. Place the adsorbed product in proper containers and remove it to a safe place. Use non-sparking tools to pick up the product. All equipment used must not be electrically grounded. For final disposal, proceed according to Section 13 of this document. Large spill: confine the liquid into a dike away from the spills for later and proper disposition. Water mist can be used to reduce of vapors, but it wont prevent ignition in closed environments.

**7 - HANDLING AND STORAGE**

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Handling the product can result in electrostatic charge buildup. All ignition sources must be extinguished from areas during use. Use proper grounding procedures. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials. Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Keep away from heat, sparks, open flame, and hot surfaces. Do not smoke. Keep the container tightly closed. Ground the container vessel and product receiver during transfers. Only use non-sparking tools. Avoid the accumulation of electrostatic charges. Use explosion-proof electrical, ventilation, and lighting equipment.
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. Packaging compatibilities: Similar to the original packaging. Keep away from incompatible materials.

**8 - EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters**

Occupational exposure limit:	The values below apply to workplaces. - <u>Carbon black:</u>
------------------------------	---

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 4/8

Cal/OSHA - PEL - TWA: 3.5 mg/m<sup>3</sup>;  
 OSHA - PEL - TWA: 3.5 mg/m<sup>3</sup> (29 CFR 1910.1000 Table Z-1) (CFR);  
 NIOSH - REL - TWA: 3.5 mg/m<sup>3</sup> (CB); 0.1 mg PAHs/m<sup>3</sup> (Ca) (AA) (AC);  
 ACGIH - TLV - TWA: 3 mg/m<sup>3</sup> (I);  
 - Zinc oxide:  
 Cal/OSHA - PEL - TWA: 5 mg/m<sup>3</sup>;  
 Cal/OSHA - PEL - STEL: 10 mg/m<sup>3</sup>;  
 OSHA - PEL - TWA: 5 mg/m<sup>3</sup> (29 CFR 1910.1000 Table Z-1) (CFR);  
 NIOSH - REL - TWA: 5 mg/m<sup>3</sup> (TD) (FM);  
 NIOSH - REL - STEL: 10 mg/m<sup>3</sup> (FM);  
 NIOSH - REL - Ceiling: 15 mg/m<sup>3</sup> (TD);  
 ACGIH - TLV - TWA: 2 mg/m<sup>3</sup> (R);  
 ACGIH - TLV - STEL: 10 mg/m<sup>3</sup> (R);  
 - Stearic acid:  
 ACGIH - TLV - TWA: 10 mg/m<sup>3</sup> (I); 3 mg/m<sup>3</sup> (R).

I: Inhalable particulate matter;  
 Ca: Potential occupational carcinogen.  
 CB: without PAHs; when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen.  
 AA: See NIOSH REL Appendix A;  
 AC: See NIOSH REL Appendix C;  
 CFR: See mentioned item in OSHA CFR;  
 TD: Total dust;  
 R: Respirable particulate matter;  
 FM: Fumes.

**Biological limit:**

- Carbon black:  
 ACGIH - BEI: Determinant: 1-Hydroxypyrene in urine. Sampling time: End of shift at the end of the workweek. Index: 2.5 ug/L, adjusted for the ratio of pyrene to benzo(a)pyrene in the polycyclic aromatic hydrocarbon (PAH) mixture to which workers are exposed. Notation: B. NOTE: H. Determinant: 3-Hydroxybenzo(a)pyrene in urine. Sampling time: End of shift at the end of the workweek. Notation: Nq.

B: The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration which could affect the interpretation of the results. Such background concentrations are incorporated in the BEI value;

Nq: Biological monitoring should be considered for this compound based on the review; however, a specific BEI could not be determined due to insufficient data;

H: The analytical method requires hydrolysis.

**Other limits and values:**

- Carbon black:  
 IDLH (NIOSH 2011): 1750 mg/m<sup>3</sup>.

**Appropriate engineering controls:**

A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the product. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.

**Individual protection measures, such as personal protective equipment (PPE)**

Hand protection: Nitrile gloves.

Eye protection: Fully enclosed protective goggles.

Skin protection: Impervious clothing or protective clothing chemically resistant to the product.

Respiratory protection: Semifacial mask with filter for organic vapors.

In compliance with OSHA HCS 29 CFR 1910.1200

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00	Date: 03/03/2025	Pages: 5/8
Physical state:	Liquid, viscous.	
Color:	Black.	
Odor:	Characteristic.	
Melting point/freezing point:	Not available.	
Boiling point (or initial boiling point or boiling range):	Not available.	
Flammability:	Flammable.	
Lower and upper explosion limit/flammability limit:	Not available.	
Flash point:	-35 °C (-31 °F) - Closed cup.	
Auto-ignition temperature:	- <u>Naphtha (petroleum), full-range straight-run:</u> 280 to 470 °C (536 to 878 °F).	
Decomposition temperature:	Not available.	
pH:	Not available.	
Kinematic viscosity:	Not available.	
Solubility:	Immiscible in water.	
Partition coefficient n-octanol/water (log value):	- <u>Naphtha (petroleum), full-range straight-run:</u> log $K_{ow}$ : 1.99 to 18.02 (calculated).	
Vapor pressure:	- <u>Naphtha (petroleum), full-range straight-run:</u> ≤ 240 kPa at 37.8 °C (100.04 °F). Not available.	
Density and/or relative density:	Not available.	
Relative vapor density:	Not available.	
Particle characteristics:	Not applicable.	
Other information:	Absolute density: 0.7 to 0.74 g/cm <sup>3</sup> at 23 °C (73.4 °F). Dynamic viscosity: 420 to 520 cP (0.42 to 0.52 Pa.s) at 23 °C (73.4 °F).	

**10 - STABILITY AND REACTIVITY**

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure.
Chemical stability:	Stable under normal temperature and pressure conditions.
Possibility of hazardous reactions, including those associated with foreseeable emergencies:	- <u>Sulfur:</u> Reacts with oxidizing agents with risk of explosion. Molten sulfur reacts with hydrocarbons to form toxic and flammable gases such as carbon disulfide and hydrogen sulfide.
Conditions to avoid:	High temperatures. Ignition sources. Contact with incompatible materials.
Incompatible materials:	Acids, aluminum, ammonia, carbon, carbon monoxide, chlorinated rubber, hydrocarbons, hydrogen, magnesium, metals, oils, oxidizing agents, phosphorus and strong oxidizers.

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 6/8

Hazardous decomposition products: No dangerous decomposition products are known.

**11 - TOXICOLOGICAL INFORMATION**

Symptoms related to the physical, chemical and toxicological characteristics: Causes skin irritation with redness, pain and dryness. May cause drowsiness or dizziness, may cause dizziness and nausea.

**Delayed and immediate effects and also chronic effects from short and long-term exposure**

Acute toxicity: Product not classified as acute toxic.  
ATEmix Vapours (4h): > 20 mg/L.  
ATEmix Dusts and mists (4h): > 5 mg/L.  
ATEmix Oral: > 5000 mg/kg.  
ATEmix Dermal: > 5000 mg/kg.

Skin corrosion/irritation: Causes skin irritation with redness, pain and dryness.

Eye damage/irritation: It is not expected to cause eye irritation.

Respiratory or skin sensitization: It is not expected to present respiratory or skin sensitization.

Germ cell mutagenicity: It is not expected to show mutagenicity in germ cells.

Carcinogenicity: It is not expected to be carcinogenic.

Reproductive toxicity: It is not expected to be reproductively toxic.

Specific target organ toxicity (single exposure): May cause drowsiness or dizziness, may cause dizziness and nausea.

Specific target organ toxicity (repeated exposure): It is not expected to exhibit specific target organ toxicity on repeated exposure.

Aspiration hazard: It is not expected to present an aspiration hazard.

**12 - ECOLOGICAL INFORMATION**

Ecotoxicity: Not classified according to the used criteria, however, it presents relevant data, as described below.

Persistence and degradability: It is not expected to present persistence and degradability.

Bioaccumulative potential: Presents high bioaccumulative potential in aquatic organisms.  
Information regarding to:  
- Naphtha (petroleum), full-range straight-run:  
BCF: 0.4 to 6280  
log  $K_{ow}$ : 1.99 to 18.02 (calculated).

Mobility in soil: Not determined.

Other adverse effects: No other environmental effects known.

**13 - DISPOSAL CONSIDERATIONS**

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 7/8

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Must be disposed of as waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product. Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.
---	---

**14 - TRANSPORT INFORMATION****International regulations****Road:** DOT - U.S. Department of Transportation.- Code of Federal Regulations.

UN number: 1133

UN proper shipping name: ADHESIVES

Transport hazard class(es): 3

Packing group: II

Environmental hazards: The product is considered dangerous for the environment for land transport.

**Sea:** IMO - International Maritime Organization:  
• IMDG Code - International Maritime Dangerous Goods Code.

UN number: 1133

UN proper shipping name: ADHESIVES

Transport hazard class(es): 3

Packing group: II

Environmental hazards: The product is considered a marine pollutant.

EmS: F-E,S-D

**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.

UN number: 1133

UN proper shipping name: ADHESIVES

Transport hazard class(es): 3

Packing group: II

Environmental hazards: The product is considered dangerous for the environment for air transport.

Transport in bulk (according to IMO instruments):	Consult regulations: <ul style="list-style-type: none"> <li>• International Maritime Organization: MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006;</li> <li>• International Maritime Organization: IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant</li> </ul>
---	--

## SAFETY DATA SHEET

**Product:** SL300 Vulk Cement Multipurpose

Revision: 00

Date: 03/03/2025

Pages: 8/8

to the code. IMO, London, 2007.

Special precautions for user: Not applicable.

**15 - REGULATORY INFORMATION**

Safety, health and environmental regulations specific for the product in question: Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

**TSCA:** We certify that all the components of this product are listed on the TSCA Inventory Active.**Prop.65:** ⚠️ WARNING: This product can expose you to Carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**16 - Other information, including date of preparation or last revision**

This document was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other products, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

**Change control:**

Version	Manufacture date	Changes
00	03/03/2025	Elaboration

**Abbreviations:**

ACGIH - American Conference of Governmental Industrial Hygienists;  
 ATEmix - Acute Toxicity Estimate of the mixture;  
 BCF - Bioconcentration factor;  
 BEI - Biological Exposure Index;  
 CAS - Chemical Abstracts Service;  
 Ceiling - The concentration that should not be exceeded during any part of the working exposure;  
 IARC - International Agency for Research on Cancer;  
 IDLH - Immediately Dangerous to Life or Health;  
 $K_{ow}$  - Octanol-water partition coefficient;  
 NIOSH - National Institute for Occupational Safety and Health;  
 OSHA - Occupational Safety & Health Administration;  
 PEL - Permissible Exposure Limit;  
 REL - Recommended Exposure Limit;  
 STEL - Short Term Exposure Limit;  
 TLV - Threshold Limit Value;  
 TWA - Time Weighted Average;  
 UN - United Nations.

**Bibliographic references:**

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2024.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.