

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Solvulk Fast Dry

Internal identification code: 480006, 480010

UFI: RMT1-E8RJ-7002-12DN

Relevant identified uses of the substance or mixture and uses advised against:

Recommended as Vulk Cement diluent.

This product must not be used for applications other than those recommended in this section.

Remove all sources of ignition. Keep away from heat, open flames, hot surfaces, sparks and not smoke.

For further information consult the technical data sheet.

1.2 Identification of the company

Manufacturer/Supplier: Vipal Europe S.L.

Amado Granell Mesado, 75, 5K-46013

Valencia, Spain

E-mail: sales.eu@vipal.com

Emergency telephone number: +34 963 25 95 10 – Frederico Schmidt

2 Hazards identification

2.1 Classification of the substance or mixture

Labelling according to Regulation (EC) No 1272/2008

Globally Harmonized System (GHS)

2.2 Label elements

Hazard pictograms



Signal word: Danger

Hazard-determining components of labelling:

Distillates (petroleum), C6-rich

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

H361 Suspected of damaging fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards: Not applicable

3 Composition/information on ingredients

3.1 Chemical characterization: Mixture

Dangerous components:

CAS	Chemical name or technical name	Concentration (%)
CAS: 93165-19-6 EINECS: 296-903-4	Distillates (petroleum), C6-rich Muta. 1A, H340; Carc. 1A, H350; Asp. Tox. 1, H304	70-100
CAS: 71-43-2 EINECS: 200-753-7	benzene Flam. Liq. 2, H225 Acute Tox. 1, H310 Muta. 1B, H340; Carc. 1A, H350; STOT RE 1, H372; Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.1

Additional information: P Note: It is not necessary to classify as a carcinogen because the substance contains less than 0,1% w / w benzene.

4 First aid measures

4.1 Description of first aid measures

After inhalation: If case of indisposition, contact the Toxicology Information Center or a doctor. Bring this MSDS. Remove the victim to fresh air. If the victim is breathing with difficult, give oxygen. if necessary administer artificial respiration. Seek medical advice.

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

After skin contact: Remove contaminated clothing. Wash exposed skin with large amounts of water for at least 30 minutes. Seek medical advice.

Do not palpate nor rub the affected area.

After eye contact: Wash immediately with running water for at least 30 minutes, keeping eyelids open. If it's possible, remove contact lenses and seek immediate medical assistance.

After swallowing: Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed:

It can cause damages to the central and peripheral nervous systems due to prolonged and repeated exposure.

Aspiration can cause pulmonary oedema and chemical pneumonitis.

It can cause damages to the cardiovascular system with tachycardia and ventricular arrhythmia.

May cause skin irritation with dryness and redness.

May cause eye irritation with tearing, pain and redness.

May cause shortness of breath, cough, dizziness drowsiness, weakness, loss of consciousness and headache.

4.3 Indication of any immediate medical attention and special treatment needed:

Avoid contact with the product when helping the victim.

If necessary, symptomatic treatment should include, above all, support measures to correction of hydro electrolytic and metabolic disturbances, and respiratory assistance.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use chemical-powder (PQS), chemical-foam, or CO₂ sprinkles. Use water-mist spout to cool down adjacencies.

Unsuitable extinguishing agents: Jet of water

5.2 Special hazards arising from the substance or mixture: The combustion of the product or its packaging can cause irritating and toxic gases, like carbon monoxide and dioxide.

It can move long distances causing retrogression of flame or new fires both in open environments such as confined.

Highly flammable product and very dangerous when exposed to excessive heat or ignition sources.

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters: Self-contained breathing apparatus (SCBA), complete protective clothing, and leather gloves.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

For people who are not part of the emergency services:

Eliminate all ignitions sources. Do not smoke.

Do not touch nor walk over spilt product.

Stay away from low areas and keep the wind to your back.

For people part of the emergency services:

Use waterproof protection clothes, nitrile gloves, closed shoes, protection goggles, and breathing mask for organic vapors.

Isolate the area in a radius of at least 50 meters, in all directions.

Stay away from low areas and keep the wind to your back.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the material and put it into adequate containers, duly labeled for further treatment and disposal.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections: No applicable

7 Handling and storage

7.1 Precautions for safe handling:

Handle the product in ventilated area or with general ventilation/exhaust system.

Ensure good ventilation/exhaustion at the workplace.

Avoid the formation of vapors or mists.

Hygienic measures: *Wash your hands before eating, drinking, smoking or using the toilet. Contaminated clothing should be changed and washed before reuse.*

7.2 Conditions for safe storage, including any incompatibilities: *Keep in a cool, covered and ventilated area, away from direct sunlight, moisture and strong sources of ozone.*

Prevention of fire and explosions: *Remove all sources of ignition. Keep away from heat, open flames, hot surfaces, sparks and not smoke.*

Inspect containers for damage or leaks before handling them.

Information about storage in one common storage facility: *Store away from foodstuffs.*

7.3 Specific end use(s): *Recommended as Vulk Cement diluent.*

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

8 Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

71-43-2 - Benzene	
ACGIH-TLVs	0,5 ppm (1,6 mg/m ³) TWA; 2,5 ppm (8 mg/m ³) STEL/CEIL - Notations: skin; A1(confirmed human carcinogen). Basis of TLV - critical effect: cancer.
NIOSH-RELs	0,1 ppm (0,32 mg/m ³) TWA; 1 ppm (3,2 mg/m ³) STEL/CEIL.
OSHA-PELs	1 ppm (3 mg/m ³) TWA; 5 ppm (15 mg/m ³) STEL/CEIL.
93165-19-6 - Distillates (petroleum), C6-rich	
ACGIH (2014) TLV-TWA	50 ppm
NIOSH (2011) REL-TWA	50 ppm
OSHA (2010) PEL-TWA	500 ppm

Ingredients with biological limit values:

93165-19-6 - Distillates (petroleum), C6-rich	
BEI (ACGIH, 2014)	2,5-hexanedione in urine: 0.4 mg/l (end of last working day)
71-43-2 - Benzene	
ACGIH - Biological determinant of exposure	S-phenylmercapturic acid in urine (1997); BEI: 25 µg/g

8.2. Exposure controls

Limitation and supervision of exposure into the environment: Steam aspiration systems must be projected in observance to local regulations concerning limits of emission of volatiles substances.

Engineering control measures: Provide mechanical ventilation and exhaust system so to maintain the vapor concentration lower than the tolerance limit.

Eye protection: Tightly sealed goggles

Protection of hands and body: Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Use waterproof clothes.

Recommended: Nitrile gloves

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Indication: breathing mask for organic vapors.

Thermal Hazards: Not applicable

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Colourless

Odour limit: Characteristic

pH: Not available

Melting point/freezing point: -95 °C (hexane)

Boiling point or initial boiling point and boiling range: 58-74 °C (hexane)

Flash point: -35 °C (closed cup - hexane)

Flammability: Not available

Lower and upper explosion limit: Lower: 1.1 Vol % (hexane) / Upper: 7.5 Vol % (hexane)

Vapour pressure: 17 kPa (hexane)

Vapour density (air=1): 3.0 (hexane)

Relative density (water=1): 0.7 (hexane)

Solubility: Insoluble (water)

Partition coefficient n-octanol/water: 3.9 log kow (hexane)

Auto-ignition temperature: 225 °C (hexane)

Decomposition temperature: Not available

Viscosity at 23 °C: 0.4 cPs (hexane)

Particle characteristics: No applicable

9.2. Other information: No further relevant information available.

10 Stability and reactivity

10.1 Reactivity: May have reactions with incompatible materials.

10.2 Chemical stability: Stable in normal use conditions.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: Elevated temperatures. Ignition sources and incompatible materials contact.

10.5 Incompatible materials: Strong agents (liquid chlorine, concentrated oxygen and dinitrogen tetroxide).

10.6 Hazardous decomposition products: A toxic gas mixture is formed upon combustion, chiefly containing CO₂ and CO.

11 Toxicological information

11.1 Information on hazard classes

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

Acute toxicity: Product not classified as acute toxic.

LD/LC50 values relevant for classification:		
93165-19-6 - Distillates (petroleum), C6-rich		
Oral	LD50	>5.000 mg/kg (rat)
Dermal	LD50	3.000 mg/kg (rat)
Inhalative	LD50/4h	> 5.000 ppm (rat)
71-43-2 - benzene		
Oral	LD50	4894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LD50/4h	9980 mg/L (mouse)

Skin corrosion/irritation: It causes skin irritation with dryness, redness, and cracks.

Serious eye damage/irritation: It can cause eye irritation accompanied by redness.

Respiratory or skin sensitization: May cause dermatitis with dryness by repeated or prolonged exposure. Not expected to give rise sensitization breathing.

Germ cell mutagenicity: It is not expected mutagenic effects in germ cells.

Carcinogenicity: Hexane: benzene concentration inferior to 0.1%, not classified as carcinogenic.

Reproductive toxicity: Suspected of damaging fertility or the unborn child.

Toxicity for specific target organ (STOT) - single exposure: It can cause respiratory tract irritation and narcotic effects with breathlessness, cough, dizziness, drowsiness, weakness, loss of consciousness and headache.

It can cause damages to the central nervous system with loss of conscience and convulsion.

Toxicity for specific target organ (STOT) - repeated exposure: It can cause damage to the central nervous system and peripheral nervous system by repeated and prolonged exposure.

Aspiration hazard: The aspiration of the product may cause pulmonary edema and chemical pneumonitis.

12 Ecological information

12.1 Toxicity: Toxic to aquatic life.

Hexane:CL50 (fish, 96h): 2.5 mg/L

12.2 Persistence and degradability: It is expected to be inherently biodegradable.

12.3 Bioaccumulative potential: It does not present bioaccumulative potential in aquatic organisms.

Hexane:

BCF:200

Log kow: 3.90

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

12.4 Mobility in soil: High mobility in soil.

12.5 Results of PBT and vPvB assessment: Not available

12.6 Endocrine disrupting properties: Not applicable

12.7 Other adverse effects: No further relevant information available.

13 Disposal considerations

13.1 Waste treatment method

Product: Treatment and disposal must be specifically evaluated for each product. The requirements of Directive 2008/98/EC, federal, state, and city laws must be consulted. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Packaging (plastic and/or cardboard), if not contaminated, should be discarded in accordance to present law.

Product remains: Keep the product remains in its original packaging. Disposal should be carried out as established for the product.

Uncleaned packaging: Disposal must be made according to official regulations.

14 Transport information

Land transport, water transportation and air transport:

Directive 2008/68/EC, on the inland transport of dangerous goods

International Maritime Organization (IMO)

International Maritime Dangerous Goods Code (IMDG Code)

International Air Transport Association (IATA)

Dangerous Goods Regulation (DGR)

14.1 UN number or ID number: UN1208

14.2 UN proper shipping name: 1208 HEXANES

14.3 Transport hazard class(es): 3 Flammable liquids

14.4 Packing group: II

14.5 Environmental hazards: The product is dangerous for the environment.

Marine pollutant: Yes

Limited quantities (LQ): 1L

EMS: F-E, S-D

14.6 Special precautions for user: Not available

14.7 Maritime transport in bulk according to IMO instruments: Not applicable

Safety Data Sheet

According to (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Version number: 102

Revision date: 03/07/2023

Trade name: Solvulk Fast Dry

15 Regulatory information

Regulations

International Maritime Organization (IMO)

International Maritime Dangerous Goods Code (IMDG Code)

International Air Transport Association (IATA)

Dangerous Goods Regulation (DGR)

Directive 2008/68/EC, on the inland transport of dangerous goods

Regulation (CE) No 1907/2006, amended by Regulation (EU) 2020/878

Regulation (EC) No 1272/2008, on classification, labelling and packaging of substances and mixtures

Directive 2008/98/EC, on waste and repealing

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This form provides information on protection, health, safety and the environment. Note that the handling of any chemical substance requires prior knowledge of its dangers to users.

The company using the product is responsible for providing training for its employees and hired parties with regards to the possible adverse risks of the product.

Data compared to the previous version altered: Compliance with Regulation (EU) 2020/878.

References:

International Uniform Chemical Information Database (IUCLID): Available in: <https://iuclid6.echa.europa.eu/>.

ECOTOX DATABASE: Available in: <https://cfpub.epa.gov/ecotox/>.

Occupational Safety and Health Administration (OSHA): Available in: < www.osha.gov >.

American Conference of Governmental Industrial Hygienists (ACGIH). Available in: <https://www.acgih.org/>.

National Institute for Occupational Safety and Health (NIOSH). Available in: <https://www.cdc.gov/niosh/index.htm>.

BR Petrobras Distribuidora. Material Safety Data Sheet, Solbrax 55/75. Revision date: 16/11/2018.

BRASKEM, Material Safety Data Sheet, Braskem Ezolem 6/7. Revision date: 15/08/2017.